

Trek Model 10/40A-HS

High-Speed High-Voltage Power Amplifier



The Model 10/40A-HS is a DC-stable, high-speed, high-voltage power amplifier used in industrial and research applications. It features an all-solid-state design for high slew rate, wide bandwidth and low-noise operation. The four-quadrant, active output stage sinks or sources current into reactive or resistive loads throughout the output voltage range. This type of output is essential to achieve an accurate output response and high slew rate demanded by a variety of loads such as highly capacitive or reactive loads. It is configured as a non-inverting amplifier.

Key Specifications

- Output Voltage Range: 0 to ± 10 kV DC or peak AC
- Output Current Range: 0 to ± 40 mA DC or 120 mA peak AC for 1 ms (must not exceed 40 mA rms max)
- Slew Rate: Greater than 900 V/ μ s
- Large Signal Bandwidth (-3 dB): DC to greater than 23 kHz, typical
- DC Voltage Gain: 1000 V/V

Typical Applications Include

- Electrostatic deflection
- Electrophoresis
- Electrorheological fluids
- Electro-optic modulation
- Material poling
- AC or DC biasing
- Ion beam steering
- Particle accelerators
- Mass spectrometers
- Material characterization
- Ferroelectrics
- Atmospheric plasma
- Dielectric barrier discharge

Features and Benefits

- Four-quadrant output for driving capacitive loads
- Closed loop system for high accuracy
- Short-circuit protected for equipment protection
- All solid-state design for maintenance free operation
- DC-stable for programmable supply applications
- Low output noise for ultra-accurate outputs
- NIST-traceable Certificate of Calibration provided with each unit



TREK, INC. • 190 Walnut Street • Lockport, NY 14094 • USA • 800-FOR TREK
716-438-7555 • 716-201-1804 (fax) • www.trekinc.com • sales@trekinc.com

Model 10/40A-HS Specifications

Performance

Output Voltage Range	0 to ± 10 kV DC or peak AC
Output Current Range	0 to ± 40 mA DC or ± 120 mA peak for 1 ms (must not exceed 40 mA rms, max)
Input Voltage Range	0 to ± 10 V DC or peak AC
Input Impedance	25 k Ω , nominal
DC Voltage Gain	1000 V/V
DC Voltage Gain Accuracy	Better than 0.1% of full scale
DC Offset Voltage	Less than ± 2 V
Output Noise	Less than 0.5 V rms*
Slew Rate (10% to 90%, typical)	Greater than 900 V/ μ s
Small Signal Bandwidth (-3dB)	DC to greater than 25 kHz
Large Signal Bandwidth (-3 dB)	DC to greater than 23 kHz, typical
Large Signal Bandwidth (1% distortion)	DC to greater than 9 kHz, typical (The unit will trip when the maximum bandwidth is reached)
Stability	
Drift with Time	Less than 50 ppm/hr, noncumulative
Drift with Temp	Less than 100 ppm/ $^{\circ}$ C

Voltage Monitor

Ratio	1/1000th of the high-voltage output signal
DC Accuracy	Better than 0.1% of full scale
DC Offset Voltage	Less than ± 2 mV
Output Noise	Less than 10 mV rms*
Output Impedance	47 Ω

Current Monitor

Ratio	1 V/12 mA
DC Accuracy	Better than 1% of full scale
Offset Voltage	Better than ± 10 mV
Output Noise	Less than 30 mV rms*
Bandwidth (-3dB)	DC to greater than 20 kHz
Output Impedance	47 Ω

Features

High-Voltage On/Off	
Local	Individual push-button switch
Remote	TTL compatible input. TTL high (or open) turns off high-voltage output. TTL low turns on high-voltage output.

Features (cont.)

Dynamic Adjustment	Graduated one-turn panel potentiometer is used to optimize the AC response for various load parameters.
Limit/Trip Mode	Switch selectable for either limit or trip. Graduated 1-turn panel potentiometer is used to adjust limit or trip level from 0 to 100% peak current. There is one LED indicator and one BNC connector
Current Trip Limit Status Indicator/ Connector	An indicator will illuminate and a BNC will provide a TTL low when the Model 10/40A-HS fails to produce the required high-voltage output such as during current limit.
Out of Regulation Status	Illuminates and a TTL low is provided when unit fails to produce required HV output such as during a current limit

Mechanical

Dimensions	279 mm H x 482 mm W 654 mm D (11" H x 19" W x 25.75" D)
Weight	24.9 kg (55 lb)
HV Connector	Alden High Voltage Connector
BNC Connectors	Amplifier Input, Voltage Monitor, Current Monitor, Remote High Voltage ON/OFF, Out of Regulation Status, Limit/Trip Status

Operating Conditions

Temperature	0 $^{\circ}$ C to 40 $^{\circ}$ C (32 $^{\circ}$ F to 104 $^{\circ}$ F)
Relative Humidity	To 85%, noncondensing
Altitude	To 2000 meters (6561.68 ft.)

Electrical

Line Voltage	Factory Set for one of two ranges: 104 to 127 V AC or 180 to 250 V AC, either at 48 to 63 Hz
AC Line Receptacle	Standard IEC 320 three-prong AC line connector
Power Consumption	1000 VA, maximum

Supplied Accessories

Operators' Manual	PN: 23462
HV Output Cable	PN: 43463
Line Cord, Spare Fuses	PN: N5011. Selected per geographic destination

*Measured using the true rms feature of the HP Model 34401A digital multimeter

Copyright © 2013 TREK, INC. All specifications are subject to change. 1322/JRB

