

Model 323

High-Sensitivity , DC Stable Electrostatic Voltmeter



Measurement Range:

0 to ± 100 V DC or peak AC

Sensitivity:

5 mV

Speed of Response:

Less than 300 ms for a
100 V step

Measurement Accuracy:

Better than 0.05% of full scale

Null Voltage Source:

10 volt nulling supply

Response Speed Control:

AC response adjusted for
speed/noise

Drift Spacing/Null Adjustment:

Minimizes variations in
voltage values as probe to
test surface spacing changes

Available Monitor Outputs:

1:1 of Voltage Monitor Output
10:1 or 20:1 (switch selectable)

*Operates with a wide
variety of Probes*

CE compliant

The Trek Model 323 Electrostatic Voltmeter performs highly sensitive voltage measurements using a variety of Trek probes with various aperture orientations (side, end) and body types (round, square). The Model 323 is a versatile instrument used for a variety of electrostatic applications including materials evaluation, electret studies, charge accumulation on disk drive assemblies, and other extremely sensitive ESD sensitive components.

The Model 323 is specifically designed for high sensitivity applications and performs highly accurate, noncontacting measurement of electrostatic potentials of 0 to 100 V over a wide range of probe-to-surface distances.

The Model 323 has adjustments to

compensate for many sensitive testing conditions. The response Speed control adjusts the speed/noise tradeoff of the AC response. The Drift/Spacing Null Adjustment minimizes the variation in zero offset voltage as the probe to test surface spacing changes.

The front panel has an easy to read 3½ digit LED display. The detected output voltage can be monitored through a 1:1 voltage monitor output and a switch selectable scale of 10:1 or 20:1 voltage monitor output.

Trek patented low impedance probes assure measurement accuracy essentially independent of probe-to-test-surface spacing, humidity conditions, and contamination such as airborne dust, toner, ions and chemicals.

CONTROL WITHOUT COMPROMISE



Model 323 Specifications

All specifications are with a Model 6000B-8 probe with a probe-to-surface separation of 1 mm.

Performance

Measurement Range

0 to ± 100 V DC or peak AC.

Sensitivity

5 mV.

Accuracy

DC Accuracy

Better than 0.05% of full scale.

Voltage Monitor Output

Better than $\pm 0.05\%$ of full scale.

Voltage Display

Better than or equal to ± 2 counts, referred to the voltage monitor.

Speed of Response (10% to 90%)

Less than 300 ms for a 100 V step (adjustable).

Stability

Drift with Time

Less than 50 ppm/hour, noncumulative.

Drift with Temperature

1:1 Monitor Output

Less than 10 mV/ $^{\circ}$ C

10:1 Monitor Output

Less than 5 mV/ $^{\circ}$ C

20:1 Monitor Output

Less than 5 mV/ $^{\circ}$ C

Features

Null Voltage Source

A calibrated 10-turn dial representing a 10 volt supply, with switch selectable polarity, used to produce zero volts output when the probe is coupled to a known zero volt surface.

Range

± 10 volts

Accuracy

1%

Resolution

20 mV.

Features (cont.)

Probe-to-Surface Separation

1.5 mm, ± 0.5 mm (recommended).

Response Speed Control

A front panel potentiometer that adjusts the speed/noise inter-relationship of the Model 323 AC response.

Voltage Display

3½ digit LED display.

Range

Switch selectable for ± 10 V or ± 100 V full scale.

Resolution

10 V Range

0.01 V.

100 V Range

0.1 V.

Zero Offset

± 2 counts, referred to the voltage monitor.

Sampling Rate

3 readings per second.

Drift/Spacing Null Adjustment

This back panel adjustment minimizes the variation in monitored voltage values as the probe to test surface spacing changes.

Voltage Monitor Output (1:1 ratio)

A buffered 0 to ± 100 V output providing a representation of the measured voltage.

Scale

1:1 of the measured voltage.

Output Noise

Less than 20 mV rms (measured using the true rms feature of the Hewlett Packard Model 34401A digital multimeter).

Output Current

5 mA.

Output Impedance

100 Ω , nominal.

Features (cont.)

Voltage Monitor Output

A buffered 0 to ± 10 V output providing a representation of the measured voltage.

Scale

10:1 of the measured voltage or

20:1 of the measured voltage

(switch selectable).

Output Current

5 mA.

Output Impedance

0.1 Ω , nominal.

General

Dimensions

108 mm H x 223 mm W x 380 mm D
(4.25" H x 8.75" W x 15" L).

Weight

3.6 kg (8 lb).

Voltage Monitor Connector

BNC coaxial connector.

Ground Receptacle

Banana jack.

AC Line Cord Receptacle

Standard three-prong line cord with integral fuse holder.

Line Supply

Factory set for one of two voltage ranges: 90 to 127 V AC or 180 to 250 V AC, at 48 to 63 Hz (specify when ordering).

Operating Conditions

Temperature

0 $^{\circ}$ C to 40 $^{\circ}$ C.

Relative Humidity

To 90%, noncondensing.

Copyright © 2003 TREK, INC.

All specifications are subject to change.
0237/JNC

Model 323 Ordering Information

Model 323 Electrostatic Voltmeter

Item	Part No.
Model 323-L (90 to 127 V AC)	323-L
Model 323-H (180 to 250 V AC)	323-H

Probes

Model 6000B-7C Probe (end-viewing, round body)	17053
Model 6000B-8 Probe (side-viewing, round body)	17054
Model 6000B-15C Probe (end-viewing, square body)	17046
Model 6000B-16 Probe (side-viewing, square body)	17047

Trek Certification

TREK, INC. certifies that each Model 323 is tested and calibrated to specifications using measurement equipment traceable to the National Institute of Standards and Technology or traceable to consensus standards. A Certificate of Calibration accompanies each instrument when it is shipped from the factory.



TREK, INC. 11601 Maple Ridge Road • Medina, NY 14103 • 800-FOR TREK
585-798-3140 • 585-798-3106 (fax) • www.trekinc.com • sales@trekinc.com

