

## TRANSPORT ROLLI



- Made of galvanized steel
- For tote boxes 600 x 800 mm
- Includes 4 swivel rubber castors  
2 with brake
- Conductive castors 100 mm Ø
- Silent and smooth operation
- Overall load bearing up to 150 kg  
for a uniformly distributed load
- ESD symbol

Part Nr.	Dimensions
<b>5390.800</b>	810 x 610 mm
<b>5390.ZS</b>	860 mm Pull rod (optional)

Typical resistance to groundable point  
 $R_{gp} = 10^3 - 10^5 \text{ ohm}$



## UTILITY CART WITH FOLDABLE HANDLE

- Stainless steel construction
- 4 conductive castors: Ø 100 mm
- Includes 4 swivel rubber castors, 2 castors with brake
- Platform fitted with dissipative rubber mat
- Overall load bearing: 100 kg for a uniformly distributed load
- ESD symbol
- **For self assembly**

Typical resistance to groundable point  
 $R_{gp} = 10^3 - 10^5 \text{ ohm}$



Webshop



Part Nr.	Dimensions
<b>5390.KW</b>	825 x 520 x 950 mm (L x W x H)

## EPA WORKSHOP TROLLEY

- Stable steel construction
- Dissipative powder coating
- Top surface with melamin coating
- 2 shelves adjustable in a 500 mm grid
- 4 drawers : 1 x 50 / 1 x 100 / 1 x 150 / 1 x 200
- Each drawer lockable / central lock with a key
- 4 conductive castors: Ø 125 mm

Typical resistance to groundable point  $R_{gp} = 10^6 - 10^8 \text{ Ohm}$

- 2 conductive swivel castors with brake
- Overall load bearing: 250 kg
- ESD symbol
- pre-assembled



Part Nr.	Dimensions
<b>5390.LW.1001</b>	1135 x 590 x 813 mm (L x W x H)

### Part Nr.

- |                          |  |
|--------------------------|--|
| <b>5390.LW.1001.659</b>  | Mats for shelf storage (Part Nr. 1452.659.* see page 19) |
| <b>5390.LW.1001.7206</b> | Rubber mat (Part Nr. 1451.7206.* see page 19)            |